



5TH EDITION DOD COALESCER CARTRIDGE

Facet's CM Series Coalescer cartridges offer the finest performance available in aviation fuel filtration for the United States Armed Forces.

This line of high flow coalescer cartridges removes ultra fine solids and enhances the optimum separation of water from Military Jet Fuel.

APPLICATIONS

Facet's CM Series elements have been tested and fully qualified to meet API/IP 1581, 5th Edition, M category, Type S in both the single stage (DOD Style) and two Stage (API style) configuration.

Designed specifically for the U.S Military, these high performance coalescers flow at a rate of 1 gallon per minute per linear inch and **directly replace** the following:

NSN 4330-01-407-3548 40" length
NSN 4330-00-983-0998 20" length

BENEFITS

- Direct replacement without modification kit
- Quick easy cartridge change out
- May be used with DOD canister and/or API Style Separator
- Removes ultra fine particulate
- Provide optimum water removal
- Multi layered media for increased solids holding capacity

STANDARD DESIGN FEATURES

- Maximum pressure rating: 75PSI
- Maximum operating temperature: 240°F
- End Caps: Top - Blind End
Bottom - Mounting End w/ O-Ring Seal
- Flow Direction: Inside/Out

Model NO.	NSN NO.	Nominal Length	Outside Diameter	Inside Diameter
		in.	in.	in.
CM420-5	4330-01-511-8268	20	3.75	1.187
CM440-5	4330-01-511-8209	40	3.75	1.187

Due to our continuing program of product improvement, specifications are subject to change without notice