

FLANGE INSULATION KITS



650 588-2241

FOR WATER, NATURAL GAS,
PETROLEUM AND
OTHER PIPE LINES.

Flange sizes 1/2" thru 96"

- * *Isolate cathodically protected lines.*
- * *Eliminate stray electrical currents in piping.*
- * *Sectionalize piping systems.*
- * *Effectively seal a flange as a gasket.*



TYPE E Full Face Gasket



TYPE F Ring Gasket

TYPICAL STANDARD KITS includes:

- * Type E (full face) gasket 1/8" thick
- or-
- * Type F (ring) gasket 1/8" thick
- * High-density polyethylene sleeves 1/32"
- * Laminated phenolic washers 1/8"
- * Steel backup washers 1/8"

Two sets of phenolic & steel washers are required when two sides are insulated.

AVAILABLE AS FOLLOWS:

- * A.S.A Series 15 - 150# Class through 2,500#
- * A.S.A Standard Gasket B16.21(4)
- * Special I.D.'s and Special O.D.'s

NOTE: When using plain phenolic flange kits, we recommend using a 1/32" or 1/16" back-up gasket on each side of the phenolic gasket for better sealing.

Options & Specifications For Calpico Flange Insulation Kits:

GASKET MATERIAL: (FF or Ring)

OPTION #1: 1/8" Phenolic manufactured from laminated phenolic sheet.

Temperature: up to 225° F.

Dielectric strength: 500 volts per mil.

Compression strength: 24,000 psi.

Water absorbance: 1.6% ASTM D-229.

OPTION #2: 1/8" Neoprene-faced phenolic.

Temperature: up to 175° F.

Dielectric strength: same as phenolic above.

Compression strength: same as phenolic above.

Water absorbance: same as phenolic above.

OPTION #3: 1/8" Fibreglas epoxy.

Temperature: up to 280° F.

Dielectric strength: 550 volts per mil.

Compression strength: 50,000 psi.

Water absorbance: 0.10%

Tensile strength: 45,000 psi.

Meets MIL-P-18177 & NEMA Grade G-10.

OPTION #4: Non-Asbestos Klinger #C4401.

Temperature: up to 400° F constant

Tensile strength: 2,000 psi ASTM F152.

OPTION #5: Non-Asbestos Garlock #3000.

Temperature: up to 400° F constant

Max pressure: 1000 psi

OPTION #6: G-10 with O-ring.

(see Option #3 for specifications.)

OPTION #7: Phenolic with O-ring.

(see Option #1 for specification.)

** Higher operating pressure will lower maximum temperature rating.

**PLEASE CONSULT FACTORY FOR APPLICATIONS INVOLVING STEAM, OR PETROLEUM.

Options cont.:

SLEEVE MATERIAL:

Option #1: 1/32" wall high density polyethylene.

Temperature: up to 175° F.

Compression: 80,000 psi

Tensile strength: 150,000 psi

Water absorbance: 0.01%

Option #2: 1/32" wall spiral-wound Mylar.

Temperature: up to 300°F.

Dielectric strength: 4,000 volts per mil.

Water absorption: 0.8%.

Option #3: 1/32" wall phenolic tubing. Specs same as gasket material.

Option #4: One-piece sleeve and washer combination. 1/32" sleeve wall and 5/32" thickness washer portion.

Option #5: 1/32" wall Fiberglas epoxy tubing. Same specs as gasket material.

Option #6: High temperature Nomex and other special sleeve material available on request.

INSULATING WASHERS:

Option #1: 1/8" phenolic, specs same as gasket material.

Option #2: 1/8" dielectric asbestos, specs same as gasket material.

Option #3: Fiberglas epoxy, specs same as gasket material.

Option #4: High temperature and special material available on request.

STEEL WASHERS:

Option #1: 1/8" thick steel made to fit within bolt facing on ASA standard flanges.

Option #2: Stainless steel available on request..

CALPICO, INC.

1387 San Mateo Ave.; So. San Francisco, CA 94080

650 588-2241 ph --- 650 873-6952 fax