



BFS/BBFS SERIES BASIC FILTRATION SYSTEMS

Multi-housing systems include wall-mounting bracket and hardware
Available with low-profile Slim Line™ or large capacity Big Blue® housings
All systems are shipped completely pre-assembled

BFS and BBFS Basic Filtration Systems consist of either two or three filter housings, which are mounted in series, a wall-mounting bracket and hardware.

The BFS-201 and BFS-301 consist of a series of 1/4" low-profile Slim Line™ housings for installations where space is limited. The BBFS systems consist of a series of large-capacity 1" #20 Big Blue® housings allowing for greater cartridge capacities and higher flow rates. All systems are equipped with a pressure relief button to relieve housing pressure during cartridge changes, and are shipped completely pre-assembled.

All of the housings are manufactured of a durable polypropylene, have excellent chemical resistance and are ideal for many residential, commercial and industrial applications.

BBFS-22

BBFS-222

BFS-301

BFS-201

Model Number	Housing Qty	Housing Size	Flow Rate* (gpm) (lpm)
BFS-201	2	1/4" Slim Line™	up to 10 gpm (37.9 lpm)
BFS-201	2	3/8" Slim Line™	up to 10 gpm (37.9 lpm)
BFS-301	3	1/4" Slim Line™	up to 10 gpm (37.9 lpm)
BBFS-22	2	1" #20 Big Blue®	up to 40 gpm (151.4 lpm)
BBFS-222	3	1" #20 Big Blue®	up to 40 gpm (151.4 lpm)

*Actual flow rate may vary and is dependent on the cartridge used.

BFS/BBFS SERIES

Basic Filtration Systems



Applications

HOME

Whole-house filtration to reduce:

- Rust Particles
- Iron (insoluble)
- Sediment
- Taste/Odor
- Chlorine

COMMERCIAL

- Deionization
- Coalescing
- Combination
- Sediment/Rust Particles
- Taste/Odor
- Duplexing

INDUSTRIAL

- Step-down Filtration
- Circulating Baths
- Plating
- Batch Treatments
- Color Reduction
- Organic Reduction
- Cooling Towers
- Pre RO Filtration
- Duplexing

System Specifications

Model	Maximum Dimensions	Maximum Pressure
BBFS-22	15-1/4" x 8-1/2" x 26-1/2" (388 mm x 216 mm x 673 mm)	90 psi (6.2 bar)
BBFS-222	23-1/4" x 8-1/2" x 26-1/2" (591 mm x 216 mm x 673 mm)	90 psi (6.2 bar)
BFS-201	10-1/2" x 5-1/4" x 14" (267 mm x 133 mm x 356 mm)	125 psi (8.62 bar)
BFS-301	15-1/2" x 5-1/4" x 14" (394 mm x 133 mm x 356 mm)	125 psi (8.62 bar)

Materials of Construction

- **Cap** Polypropylene
- **Housing** Polypropylene
- **Bracket** Powder Coated Carbon Steel
- **O-Rings** Buna-N
- **Maximum Temperature** 100°F (37.8°C)

NOTE: 20" (508 mm) Big Blue® sumps are interchangeable with 10" (254 mm) Big Blue® sumps.

NOTE: Big Blue® (BB®) is a registered trademark of USFilter Consumer and Commercial.

WARNING: For drinking water applications, do not use with water that microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

CAUTION: Filter must be protected against freezing, which can cause cracking of the filter and water leakage.



502 Indiana Avenue • Sheboygan, WI 53081
 USA/Canada: 800-645-0267 phone • 800-882-6652 fax
 International: 920-451-9322 phone • 920-457-2417 fax

www.plymouthwater.com
 Printed in U.S.A. 05/01 310089 Rev A